

## 595RS-R - Global Market Dimension Data (30/35/40/45/50)

SER	Size	PR	LVSS	Overall		Section		Standard	Approved	Tread		Tread		Weight	MAX.	Max	UTQG	Sidewall Type	
				Diameter		Width		Rim	Rim Width	Width		Depth			PSI	Load			
				mm	in	mm	in	in	in	mm	in	in32"	mm		KG	COLD			KGS
30	285/30ZR18		97W XL	626	24.6	290	11.4	10	9.5-10.5	259	10.2	8	6.2	13.1	50	730	1609	140AA A	BSW
35	245/35ZR18		88W	627	24.7	248	9.8	8.5	8-9	224	8.8	8	6.5	11.7	44	560	1234	140AA A	BSW
	255/35ZR18		90W	634	25	260	10.2	9	8.5-9.5	236	9.3	8	6.5	12.5	44	600	1323	140AA A	BSW
	265/35ZR18		93W	643	25.3	271	10.7	9.5	9-10	246	9.7	8	6.5	12.9	44	650	1433	140AA A	BSW
40	215/40ZR17		83W	603	23.7	222	8.7	7.5	7-8.5	190	7.5	9	7.5	10	44	467	1074	140AA A	BSW
	235/40ZR17		90W	619	24.4	238	9.4	8.5	8-9.5	216	8.5	8	6.5	11.3	44	600	1323	140AA A	BSW
	255/40ZR17		94W	634	25	260	10.2	9	8.5-10	232	9.1	8	6.5	12.4	44	670	1477	140AA A	BSW
	225/40ZR18		88W	636	25	231	9.1	8	7.5-8.5	204	8	8	6.5	11	44	560	1235	140AA A	BSW
	235/40ZR18		91W	643	25.3	240	9.4	8.5	8-9	218	8.6	8	6.5	12.3	44	615	1356	140AA A	BSW
45	205/45ZR16		83W	589	23.2	209	8.2	7	6.5-7.5	188	7.4	8	6.5	9.7	44	487	1073	140AA A	BSW
	215/45ZR17		87W	625	24.6	219	8.6	7	6.5-7.5	196	7.7	8	6.5	11.1	44	545	1201	140AA A	BSW
	225/45ZR17		94W XL	633	24.9	230	9.1	7.5	7-8	206	8.1	7	5.2	11.3	50	670	1477	140AA A	BSW
	235/45ZR17		94W	643	25.3	240	9.4	8	7.5-8.5	212	8.3	8	6.5	11.8	44	670	1477	140AA A	BSW
50	195/50ZR15		82W	577	22.7	200	7.9	6	5.5-6.5	176	6.9	8	6.5	9.2	44	475	1047	140AA A	BSW
	205/50ZR15		89W XL	589	23.2	210	8.3	6.5	6-7	182	7.2	8	6.5	9.8	50	580	1279	140AA A	BSW
	205/50ZR16		87W	610	24	210	8.3	6.5	6-7	182	7.2	8	6.5	10.1	44	545	1201	140AA A	BSW

\*These data can be changed by manufacturer without prior notice.

Update: 2016/03/31