

# Formoza AZ01 - Global Market Dimension Data (40/45/50/55/60/65)

SER	Size	PR	LI/SS	Overall		Section		Standard	Approved	Tread		Tread		Weight	MAX.	Max		UTQG	Sidewall Type
				Diameter		Width		Rim	Rim Width	Width		Depth			PSI	Load			
				mm	in	mm	in	in	in	mm	in	in32"	mm		KG	COLD	KGS		
40	245/40ZR17		91W	632	24.9	243	9.6	8.5	8-9.5	206	8.1	9	7	10.9	44	615	1356	380A A	BSW
	225/40ZR18		92W XL	640	25.2	226	8.9	8	7.5-9	190	7.5	10	7.6	11.1	50	630	1389	380A A	BSW
	235/40ZR18		95W XL	647	25.5	238	9.4	8.5	8-9.5	200	7.9	10	7.6	11	50	690	1521	380A A	BSW
	245/40ZR18		93W	658	25.9	243	9.6	8.5	8-9.5	205	8.1	9	7	12.5	44	650	1433	380A A	BSW
45	195/45R16		84V XL	585	23	193	7.6	6.5	6-7.5	156	6.1	10	7.9	7.8	50	500	1102	380A A	BSW
	205/45ZR16		87W XL	595	23.4	205	8.1	7	6.5-7.5	170	6.7	10	7.7	8.7	50	545	1201	380A A	BSW
	215/45ZR17		91W XL	626	24.6	210	8.3	7	7-8	170	6.7	10	7.6	9.5	50	615	1356	380A A	BSW
	225/45ZR17		91W	637	25.1	223	8.8	7.5	7-8.5	180	7.1	10	7.7	9.6	44	615	1356	380A A	BSW
	235/45ZR17		97W XL	647	25.5	231	9.1	8	7.5-9	188	7.4	10	7.6	10.1	50	730	1609	380A A	BSW
	245/45ZR17		95W	653	25.7	240	9.4	8	7.5-9	194	7.6	9	7	11.4	44	690	1521	380A A	BSW
	225/45ZR18		95W XL	663	26.1	220	8.7	7.5	7-8.5	180	7.1	10	7.6	10.8	50	690	1521	380A A	BSW
50	245/45ZR18		100W XL	679	26.7	240	9.5	8	7.5-9	194	7.6	9	7	11.6	44	800	1764	380A A	BSW
	195/50R15		82V	576	22.7	194	7.6	6	5.5-7	156	6.1	10	7.9	7.6	44	475	1047	380A A	BSW
	205/50R15		86V	587	23.1	207	8.1	6.5	5.5-7.5	166	6.5	10	7.9	8.8	44	750	1653	380A A	BSW
	165/50R16		75V	576	22.7	168	6.6	5	4.5-6	133	5.2	9	7.2	6.6	44	387	853	380A A	BSW
	195/50R16		84V	602	23.7	196	7.7	6	5.5-7	156	6.1	10	7.9	8.1	44	500	1102	380A A	BSW
	205/50R16		87V	612	24.1	209	8.2	6.5	5.5-7.5	166	6.5	10	7.9	9.3	44	545	1201	380A A	BSW
	225/50ZR16		92W	631	24.8	232	9.1	7	6-8	181	7.1	10	7.6	10.6	44	630	1388	380A A	BSW
	205/50ZR17		93W XL	637	25.1	214	8.4	6.5	5.5-7.5	179	7	10	7.6	10.6	50	650	1433	380A A	BSW
	215/50ZR17		95W XL	649	25.6	221	8.7	7	6-7.5	176	6.9	10	7.6	10.3	50	690	1521	380A A	BSW
55	225/50ZR17		98W XL	656	25.8	236	9.3	7	6-8	196	7.7	10	7.6	11.2	50	750	1653	380A A	BSW
	165/55R15		75V	566	22.3	168	6.6	5	4.5-6	133	5.2	9	7.2	6.4	44	387	853	380A A	BSW
	175/55R15		77H	578	22.8	180	7.1	5.5	5-6	120	4.7	10	7.6	7.1	44	412	908	380A A	BSW
	185/55R15		82H	587	23.1	191	7.5	6	5-6.5	151	5.9	10	7.9	7.6	44	475	1047	380A A	BSW
	195/55R15		85V	593	23.3	202	8	6	5.5-7	156	6.1	10	7.6	8.4	44	515	1135	380A A	BSW
	205/55R15		88V	606	23.9	212	8.3	6.5	5.5-7.5	166	6.5	10	7.9	8.4	44	560	1235	380A A	BSW
	185/55R16		83V	611	24.1	192	7.5	6	5-6.5	151	5.9	10	7.9	8.4	44	487	1074	380A A	BSW
	195/55R16		87V	619	24.4	200	7.9	6	5.5-7	156	6.1	10	7.9	8.7	44	545	1201	380A A	BSW
	205/55R16		91V	636	25	209	8.2	6.5	5.5-7.5	176	6.9	10	7.9	9.9	44	615	1356	380A A	N/A
	205/55ZR16		94W XL	631	24.8	209	8.2	6.5	5.5-7.5	176	6.9	10	7.9	9.8	50	670	1477	380A A	BSW
215/55ZR16		97W XL	645	25.4	224	8.8	7	6-7.5	176	6.9	10	7.6	10.6	50	730	1609	380A A	BSW	

SER	Size	PR	LI/SS	Overall		Section		Standard	Approved	Tread		Tread		Weight	MAX.	Max		UTQG	Sidewall
				Diameter		Width		Rim	Rim Width	Width		Depth			PSI	Load			Type
				mm	in	mm	in	in	in	mm	in	in32"	mm		KG	COLD	KGS		
	225/55ZR16		99W XL	657	25.9	230	9.1	7	6-8	181	7.1	10	7.6	10.8	50	775	1709	380A A	BSW
	205/55R17		91V	657	25.9	210	8.3	6.5	5.5-7.5	166	6.5	9	7.3	9.7	44	615	1356	380A A	BSW
	215/55R17		94V	666	26.2	225	8.9	7	6-7.5	176	6.9	10	7.6	10.1	44	670	1471	380A A	BSW
	225/55ZR17		101W XL	678	26.7	233	9.2	7	6-8	192	7.6	10	7.9	11.5	50	825	1819	380A A	BSW
60	155/60R15		74H	543	21.4	152	6	4.5	4.5-5.5	120	4.7	9	7.5	6.2	44	375	827	380A A	BSW
	185/60R15		84H	609	24	187	7.4	5.5	5-6.5	140	5.5	10	7.9	7.8	44	500	1102	380A A	BSW
	195/60R15		88H	614	24.2	198	7.8	6	5.5-7	152	6	10	7.9	8.1	44	560	1233	380A A	BSW
	205/60R15		91V	626	24.6	205	8.1	6	5.5-7.5	158	6.2	10	8.1	8.7	44	615	1355	380A A	BSW
	195/60R16		89H	640	25.2	198	7.8	6	5.5-7	152	6	10	7.9	8.8	44	580	1279	380A A	BSW
	205/60R16		92V	650	25.6	208	8.2	6	5.5-7.5	158	6.2	10	8.1	9.1	44	630	1389	380A A	BSW
	215/60R16		99V XL	664	26.1	221	8.7	6.5	6-7.5	168	6.6	10	7.6	10	50	630	1389	380A A	BSW
	225/60R16		98V	678	26.7	224	8.8	6.5	6-8	170	6.7	9	7.3	11.2	44	750	1654	380A A	BSW
	215/60R17		96H	690	27.1	219	8.6	6.5	6-7.5	168	6.6	10	7.6	11	44	710	1565	380A A	BSW
65	175/65R15		84H	611	24.1	175	6.9	5	5-6	129	5.1	10	7.9	7.7	44	500	1102	380A A	BSW
	195/65R15		91V	632	24.9	203	8	6	5.5-7	146	5.7	10	8.1	9.8	44	615	1356	380A A	BSW
	205/65R15		95H	649	25.6	204	8	6	5.5-7.5	152	6	10	8.2	10	44	690	1251	380A A	BSW
	215/65R16		98H	687	27	220	8.7	6.5	6-7.5	161	6.3	10	7.6	10.6	44	750	1653	380A A	BSW

\*These data can be changed by manufacturer without prior notice.

Update: 2016/03/31