

## Formoza FD2 - Global Market Dimension Data (30/35/40/45/50/55/60/65)

SER	Size	PR	L/SS	Overall		Section		Standard	Approved	Tread		Tread		Weight	MAX.	Max		UTQG	Sidewall Type
				Diameter		Width		Rim	Rim Width	Width		Depth			PSI	Load			
				mm	in	mm	in	in	in	mm	in	in32"	mm		KG	COLD	KGS		
30	225/30ZR20		85W XL	645	25.4	228	9	8	7.5-8.5	211	8.3	10	8.1	10.6	50	515	1135	420A A	BSW
	245/30ZR20		90W XL	658	25.9	244	9.6	8.5	8-9	225	8.8	10	8.2	10.9	50	600	1323	420A A	BSW
35	225/35ZR20		95W XL	666	26.2	226	8.9	8	7.5-8.5	208	8.2	10	8	11.1	50	690	1521	420A A	BSW
	245/35ZR20		95W XL	680	26.8	249	9.8	8.5	8-9	228	9	10	8.2	12.1	50	690	1521	420A A	BSW
40	215/40ZR17		83W	607	23.9	215	8.5	7.5	7-8.5	180	7.1	10	7.6	8.9	44	487	1073	420A A	BSW
	215/40ZR18		85W	628	24.7	222	5.1	7.5	7-8	198	7.8	10	8.3	10	44	515	1135	420A A	BSW
	225/40ZR18		92W XL	637	25.1	231	9.1	8	7.5-8.5	208	8.2	10	8.1	11.3	50	630	1389	420A A	BSW
	245/40ZR19		98W XL	680	26.8	249	9.8	8.5	8-9	225	8.8	10	8.2	11.7	50	750	1653	420A A	BSW
	255/40ZR19		100Y XL	687	27	260	10.2	9	8.5-9.5	236	9.3	10	8.2	13.1	50	800	1764	420A A	BSW
45	205/45ZR16		87W XL	590	23.2	207	8.2	7	6.5-7.5	185	7.3	10	8.3	9.1	50	545	1201	420A A	BSW
	215/45ZR17		91W XL	626	24.6	212	8.4	7	7.5-8.5	209	8.2	11	8.5	9.5	50	615	1356	420A A	BSW
	225/45ZR17		94W XL	634	25	225	8.9	7.5	7-8.5	201	7.9	11	8.4	11	50	670	1477	420A A	BSW
	235/45ZR17		97W XL	644	25.4	235	9.3	8	7.5-8.5	209	8.2	11	8.5	11.3	50	730	1609	420A A	BSW
	245/45ZR17		95W	652	25.7	238	9.4	8	7.5-9	201	7.9	9	7	10.6	44	690	1521	420A A	BSW
	215/45ZR18		93W XL	654	25.8	212	8.3	7	6.5-7.5	190	7.5	11	8.4	10.9	50	650	1433	420A A	BSW
	225/45ZR18		95W XL	659	25.9	228	9	7.5	7-8	201	7.9	11	8.5	11.3	50	690	1521	420A A	BSW
	245/45ZR18		96W	678	26.7	240	9.4	8	7.5-9	201	7.9	9	7	11.4	44	710	1565	420A A	BSW
50	225/50ZR16		96W XL	630	24.8	229	9	7	6.5-7.5	202	8	11	8.4	11.2	50	710	1565	420A A	BSW
	205/50R17		89V	639	25.1	211	8.3	6.5	5.5-7.5	179	7	10	7.6	9.5	44	580	1279	420A A	BSW
	215/50ZR17		95W XL	648	25.5	226	8.9	7	6.5-7.5	195	7.7	11	8.4	11.5	50	690	1521	420A A	BSW
	235/50ZR17		96W	667	26.3	247	9.7	7.5	7-8	212	8.3	11	8.6	11.7	44	710	1565	420A A	BSW
	225/50ZR18		95W	688	27.1	228	9	7	6-8	180	7.1	10	7.9	11.4	44	690	1521	420A A	BSW
55	195/55R15		85V	594	23.4	203	8	6	5.5-6.5	174	6.9	10	8.2	8.6	44	515	1135	420A A	BSW
	205/55ZR16		94W XL	631	24.8	215	8.5	6.5	6-7	190	7.5	10	8.3	10	50	670	1477	420A A	BSW
	215/55ZR16		97W XL	640	25.2	229	9	7	6.5-7.5	194	7.6	11	8.4	11.1	50	730	1607	420A A	BSW
	225/55ZR16		99W XL	653	25.7	239	9.4	7	6.5-7.5	198	7.8	11	8.4	11.5	50	775	1709	420A A	BSW
	205/55ZR17		95Y XL	658	25.9	214	8.4	6.5	5.5-7.5	185	7.3	11	8.6	11.1	50	690	1521	420A A	BSW
	215/55ZR17		98W XL	668	26.3	228	9	7	6.5-7.5	194	7.6	11	8.4	10.9	50	750	1653	420A A	BSW
	225/55ZR17		101W XL	680	26.8	233	9.2	7	6.5-7.5	203	8	11	8.4	11.8	50	825	1819	420A A	BSW
	235/55ZR17		103W XL	691	27.2	249	9.8	7.5	7-8	208	8.2	11	8.4	12.4	50	875	1929	420A A	BSW
	235/55R18		100V	715	28.1	246	9.7	7.5	6.5-8.5	201	7.9	10	8.3	13.3	44	800	1763	420A A	BSW

SER	Size	PR	L/SS	Overall		Section		Standard	Approved	Tread		Tread		Weight	MAX.	Max		UTQG	Sidewall Type
				Diameter		Width		Rim	Rim Width	Width		Depth			PSI	Load			
				mm	in	mm	in	in	in	mm	in	in32"	mm		KG	COLD	KGS		
60	185/60R14		82H	579	22.8	185	7.3	5.5	5-6	160	6.3	10	8.1	7.5	44	475	1047	420A A	BSW
	195/60R14		86H	591	23.3	200	7.9	6	5.5-6.5	168	6.6	10	8.2	8.2	44	530	1168	420A A	BSW
	195/60R15		88V	614	24.2	202	7.9	6	5.5-6.5	168	6.6	10	8.2	8.9	44	560	1235	420A A	BSW
	205/60R15		91V	627	24.7	207	8.1	6	5.5-6.5	175	6.9	10	8.2	9.9	44	615	1356	420A A	BSW
	215/60R15		94V	639	25.1	214	8.4	6.5	6-7	184	7.2	11	8.4	10.3	44	670	1477	420A A	BSW
	175/60R16		82H	618	24.3	177	6.9	5	4.5-5.5	150	5.9	10	7.9	7.8	44	475	1047	420A A	BSW
	205/60R16		92V	651	25.6	209	8.2	6	5.7-7.5	165	6.5	11	8.6	9.2	44	630	1389	420A A	BSW
	215/60R16		95V	664	26.1	221	8.7	6.5	6-7.5	174	6.9	11	8.4	11.2	44	690	1521	420A A	BSW
	215/60R16		99V XL	664	26.1	221	8.7	6.5	6-7.5	174	6.9	11	8.4	10.7	50	775	1709	420A A	BSW
	225/60R16		98V	676	26.6	226	8.9	6.5	6-7	190	7.5	11	8.4	11.5	44	750	1653	420A A	BSW
	235/60R16		100H	692	27.3	234	9.2	7	6.5-8.5	179	7	10	8.3	11.6	44	800	1763	420A A	BSW
	215/60R17		96H	689	27.1	223	8.8	6.5	6-7	174	6.9	11	8.8	11.3	44	710	1565	420A A	BSW
	225/60R17		99H	709	27.9	219	8.6	6.5	6-8	178	7	10	8.2	12	44	775	1078	420A A	BSW
	225/60R18		100H	729	28.7	229	9	6.5	6-8	170	6.7	10	8.3	12.4	44	800	1764	420A A	BSW
65	155/65R14		75H	561	22.1	150	5.9	4.5	4.5-5.5	119	4.7	10	7.7	6.1	44	387	853	420A A	BSW
	185/65R14		86H	596	23.5	191	7.5	5.5	5-6	160	6.3	10	8	7.9	44	530	1168	420A A	BSW
	195/65R15		91V	635	25	201	7.9	6	5.5-6.5	168	6.6	10	8.1	9.8	44	615	1356	420A A	BSW
	205/65R15		95V	647	25.5	210	8.3	6	5.5-6.5	175	6.9	10	8.2	10.3	44	690	1521	420A A	BSW
	215/65R15		96V	661	26	221	8.7	6.5	6-7.5	167	6.6	10	8.3	10.8	44	710	1565	420A A	BSW
	205/65R16		95V	672	26.5	209	8.2	6	5.5-6.5	175	6.9	10	8.2	10.5	44	690	1521	420A A	BSW
	215/65R16		98V	687	27	223	8.8	6.5	6-7.5	186	7.3	10	8.3	12.2	44	750	1653	420A A	BSW
	225/65R16		100H	701	27.6	226	8.9	6.5	6-8	166	6.5	11	8.4	11.6	44	800	1764	420A A	BSW
	235/65R16		103H	712	28	243	9.6	7	6.5-8.5	184	7.2	10	7.6	11.5	44	875	1929	420A A	BSW
	215/65R17		99H	714	28.1	220	8.7	6.5	6-7.5	162	6.4	10	8.3	11.8	44	775	1709	420A A	BSW

\*These data can be changed by manufacturer without prior notice.

Update: 2016/03/31