

## 595RPM - Global Market Dimension Data (25/30/35/40/45/50)

SER	Size	PR	LVSS	Overall		Section		Standard	Approved	Tread		Tread		Weight	MAX.	Max	UTQG	Sidewall Type	
				Diameter		Width		Rim	Rim Width	Width		Depth			PSI	Load			
				mm	in	mm	in	in	in	mm	in	in32"	mm		KG	COLD			KGS
25	295/25ZR21		96Y XL	681	26.8	295	11.6	10.5	10-11	277	10.9	11	8.4	15.2	50	710	1565	160AA A	BSW
30	335/30ZR20		104Y	706	27.8	345	13.6	12	11.5-12.5	309	12.2	10	7.6	16.4	44	900	1985	160AA A	BSW
	255/30ZR21		93Y XL	685	27	256	10.1	9	8.5-9.5	236	9.3	10	8.2	13.1	50	650	1433	160AA A	BSW
35	265/35ZR18		97Y XL	643	25.3	267	10.5	9.5	9-10.5	247	9.7	10	7.6	12.1	50	730	1609	160AA A	BSW
	225/35ZR19		88Y XL	639	25.1	231	9.1	8	7.5-9	208	8.2	10	8.2	11	50	560	1235	160AA A	BSW
	235/35ZR19		91Y XL	646	25.4	242	9.5	8.5	8-9.5	218	8.6	10	7.9	10.8	50	615	1356	160AA A	BSW
	245/35ZR19		93Y XL	655	25.8	244	9.6	8.5	8-9.5	224	8.8	10	8.2	11.5	50	650	1433	160AA A	BSW
	255/35ZR19		96Y XL	660	26	261	10.3	9	8.5-10	238	9.4	10	7.6	12.5	50	710	1565	160AA A	BSW
	265/35ZR19		98Y XL	668	26.3	268	10.5	9.5	9-10.5	234	9.2	10	8.2	12.6	50	750	1653	160AA A	BSW
	285/35ZR19		99Y	683	26.9	292	11.5	10	9.5-11	260	10.2	11	8.5	14	44	775	1709	160AA A	BSW
	245/35ZR21		96W XL	703	27.7	249	9.8	8.5	8-9.5	227	8.9	10	8.2	13	50	710	1566	160AA A	BSW
40	225/40ZR18		92Y XL	634	25	231	9.1	8	7.5-9	213	8.4	10	8.1	11.5	50	630	1389	160AA A	BSW
	235/40ZR18		91Y	643	25.3	239	9.4	8.5	8-9.5	212	8.3	10	8.1	11	44	615	1356	160AA A	BSW
	245/40ZR18		97Y XL	651	25.6	248	9.8	8.5	8-9.5	218	8.6	10	8.1	11.8	50	730	1609	160AA A	BSW
	225/40ZR19		93Y XL	662	26.1	232	9.1	8	7.5-9	202	8	10	8.2	10.7	50	650	1433	160AA A	BSW
	255/40ZR19		96Y	686	27	260	10.2	8.5	8.5-10	231	9.1	10	8.2	12.9	44	710	1565	160AA A	BSW
45	215/45ZR17		91Y XL	625	24.6	215	8.5	7	7-8	191	7.5	10	8	10.4	50	615	1356	160AA A	BSW
	245/45ZR18		96Y	677	26.6	239	9.4	8	7.5-9	216	8.5	10	7.9	12.7	44	710	1565	160AA A	BSW
	255/45ZR18		99Y	686	27	256	10.1	8.5	8-9.5	227	8.9	10	8.2	13.1	44	775	1709	160AA A	BSW
50	245/50ZR18		100W	703	27.7	248	9.8	7.5	7-8.5	215	8.5	10	7.9	13.1	44	800	1764	160AA A	BSW

\*These data can be changed by manufacturer without prior notice.

Update: 2016/03/31