

Formoza GIO - Global Market Dimension Data (45/50/55/60/65/70/80)

SER	Size	PR	LVSS	Overall		Section		Standard	Approved	Tread		Tread		Weight	MAX.	Max		UTQG	Sidewall Type
				Diameter		Width		Rim	Rim Width	Width		Depth			PSI	Load			
				mm	in	mm	in	in	in	mm	in	in32"	mm	KG	COLD	KGS	LBS		
45	165/45R15		68V	533	21	164	6.4	5.5	5-6	137	5.4	9	7.3	5.8	44	315	694	420A A	BSW
50	165/50R15		73V	552	21.7	164	6.4	5	4.5-6	133	5.2	9	7.2	6.3	N/A	N/A	N/A	420A A	BSW
55	155/55R14		69V	530	20.9	163	6.4	5	4.5-5.5	126	5	9	7.3	5.7	N/A	N/A	N/A	420A A	BSW
	165/55R14		72V	538	21.2	171	6.7	5	4.5-6	133	5.2	9	7.3	6.1	44	355	783	420A A	BSW
60	165/60R14		75H	558	22	165	6.5	5	4.5-6	122	4.8	8	6.6	6.1	44	387	853	420A A	BSW
	175/60R14		79H	564	22.2	176	6.9	5	5-6	127	5	9	7	6.5	44	437	963	420A A	BSW
	185/60R14		82H	578	22.8	189	7.4	5.5	5-6.5	136	5.4	9	7.4	6.9	44	475	1047	420A A	BSW
	185/60R15		84H	609	24	187	7.4	5.5	5-6.5	140	5.5	10	7.9	7.5	44	500	1102	420A A	BSW
	195/60R15		88H	N/A	N/A	N/A	N/A	6	N/A	N/A	N/A	N/A	N/A	8.2	44	560	1234	420A A	BSW
	205/60R15		91H	629	24.8	208	8.2	6	5.5-7.5	150	5.9	10	7.7	8.5	44	615	1355	420A A	BSW
	225/60R15		96V	651	25.6	222	8.8	6.5	6-8	173	6.8	10	8	10.4	44	710	1565	420A A	BSW
	205/60R16		92H	657	25.9	204	8	6	5.5-7.5	150	5.9	10	7.7	9.5	44	630	1388	420A A	BSW
	215/60R16		95H	668	26.3	218	8.6	6.5	6-7.5	167	6.6	10	7.7	9.9	44	690	1521	420A A	BSW
	225/60R16		98H	673	26.5	227	8.9	6.5	6-8	173	6.8	10	8	11.1	44	750	1653	420A A	BSW
65	155/65R13		73T	534	21	152	6	4.5	4.5-5.5	114	4.5	8	6.2	5.5	44	365	804	420A A	BSW
	165/65R13		77H	546	21.5	168	6.6	5	4.5-6	124	4.9	8	6.2	6	44	412	908	420A A	BSW
	175/65R13		80T	556	21.9	177	7	5	5-6	128	5	9	7.2	6.2	44	450	992	420A A	BSW
	165/65R14		79T	575	22.6	168	6.6	5	4.5-6	124	4.9	8	6.2	6.2	44	437	963	420A A	BSW
	175/65R14		82H	582	22.9	176	6.9	5	5-6	128	5	9	7.2	6.9	44	475	1047	420A A	BSW
	185/65R14		86H	598	23.5	191	7.5	5.5	5-6.5	138	5.4	9	7.2	7.4	44	530	1168	420A A	BSW
	195/65R14		89H	609	24	199	7.8	6	5.5-7	144	5.7	9	7.2	7.7	44	580	1278	420A A	BSW
	185/65R15		88H	626	24.6	190	7.5	5.5	5-6.5	138	5.4	9	7.2	7.6	44	560	1234	420A A	BSW
	195/65R15		91H	633	24.9	199	7.8	6	5.5-7	144	5.7	9	7.2	8.2	44	615	1355	420A A	BSW
	205/65		95H	648	25.5	209	8.2	6	5.5-7	150	5.9	10	7.6	9.6	44	690	1521	420A A	BSW
215/65R15		96H	659	25.9	221	8.7	6.5	6-7.5	160	6.3	10	7.6	9.7	44	710	1565	420A A	BSW	
70	155/70R13		75T	547	21.5	153	6	4.5	4-5	113	4.4	9	7.3	5.4	44	387	853	420A A	BSW
	165/70R13		79T	560	22	165	6.5	5	4.5-5.5	122	4.8	9	7.3	6.1	44	437	963	420A A	BSW
	175/70R13		82H	575	22.6	175	6.9	5	4.5-6	127	5	9	7.5	6.9	44	475	1047	420A A	BSW
	165/70R14		81T	584	23	166	6.5	5	4.5-5.5	120	4.7	9	7.3	6.5	44	462	1018	420A A	BSW
	175/70R14		84H	599	23.6	175	6.9	5	4.5-6	125	4.9	9	7.5	6.7	N/A	N/A	N/A	420A A	BSW
	185/70R14		88H	612	24.1	186	7.3	5.5	4.5-6	134	5.3	10	7.9	7.5	44	560	1234	420A A	BSW

SER	Size	PR	LVSS	Overall		Section		Standard	Approved	Tread		Tread		Weight	MAX.	Max		UTQG	Sidewall Type
				Diameter		Width		Rim	Rim Width	Width		Depth			PSI	Load			
				mm	in	mm	in	in	in	mm	in	in32"	mm	KG	COLD	KGS	LBS		
	195/70R14		91H	626	24.6	197	7.7	6	5-6.5	142	5.6	10	7.9	8.5	44	615	1355	420A A	BSW
80	155/80R13		79T	577	22.7	159	6.2	4.5	4-5	113	4.4	9	7	6.3	44	437	963	420A A	BSW

*These data can be changed by manufacturer without prior notice.

Update: 2016/03/31