

SS657 - Global Market Dimension Data (60/65/70/80)

SER	Size	PR	L/SS	Overall		Section		Standard	Approved	Tread		Tread		Weight	MAX.	Max		UTQG	Sidewall Type
				Diameter		Width		Rim	Rim Width	Width		Depth			PSI	Load			
				mm	in	mm	in	in	in	mm	in	in32"	mm	KG	COLD	KGS	LBS		
60	175/60R13		77H	542	21.4	171	6.7	5	4.55.5	140	5.5	10	7.6	6.1	44	412	908	420A A	BSW
	185/60R13		80H	553	21.8	192	7.5	5.5	56	152	6	10	7.9	7.1	44	450	992	420A A	BSW
	205/60R13		87H	576	22.7	210	8.3	6	5.57	168	6.6	10	8.1	8.8	44	545	1202	420A A	BSW
	165/60R14		75H	553	21.8	173	6.8	N/A	N/A	N/A	N/A	N/A	N/A	6.2	N/A	N/A	N/A	N/A	BSW
	175/60R14		79H	566	22.3	175	6.9	5	4.55.5	140	5.5	9.1	7.3	7	44	437	963	420A A	BSW
	185/60R14		82H	581	22.9	184	7.2	5.5	5-6	148	5.8	10	8	7.2	44	475	1047	420A A	BSW
	195/60R14		86H	590	23.2	190	7.5	6	5.5-6.5	156	6.1	10	7.9	7.6	44	530	1168	420A A	BSW
	205/60R14		89H	605	23.8	202	8	6	5.5-6.5	164	6.5	10	8.3	8.6	44	580	1279	420A A	BSW
	185/60R15		84H	607	23.9	184	7.2	5.5	5-6	148	5.8	10	8	7.7	44	500	1102	420A A	BSW
	195/60R15		88H	615	24.2	202	8	6	5.5-6.5	156	6.1	10	7.9	8.3	44	560	1234	420A A	BSW
	205/60R15		91H	628	24.7	206	8.1	6	5.5-6.5	168	6.6	11	8.4	9.1	44	615	1356	420A A	BSW
	215/60R15		94H	642	25.3	218	8.6	6.5	6-7	172	6.8	11	8.5	10.1	44	670	1477	420A A	BSW
	225/60R15		96H	651	25.6	223	8.8	6.5	6-7	180	7.1	11	8.6	10.4	44	710	1565	420A A	BSW
	205/60R16		92H	653	25.7	203	8	6	5.5-6.5	164	6.5	11	8.4	9.6	44	630	1389	420A A	BSW
	215/60R16		95H	664	26.2	221	8.7	6.5	6-7	172	6.8	11	8.6	10.4	44	690	1521	420A A	BSW
	225/60R16		105H XL	678	26.7	226	8.9	6.5	6-7	184	7.2	11	8.7	11.9	50	925	2039	420A A	RWL
	225/60R16		98H	678	26.7	228	9	6.5	6-8	184	7.2	11	8.7	11.3	44	750	1653	420A A	BSW
	235/60R16		100H	691	27.2	236	9.3	7	6.5-7.5	187	7.4	11	8.8	12	44	800	1764	420A A	BSW
65	155/65R13		73T	532	20.9	158	6.2	4.5	4.5-5.5	121	4.8	10	7.7	5.5	44	365	805	420A A	BSW
	165/65R13		77T	545	21.5	160	6.3	5	4.5-6	124	4.9	10	7.6	6.4	44	412	908	420A A	BSW
	175/65R13		80T	557	21.9	176	6.9	5	5-6	130	5.1	10	7.7	6.7	44	450	992	420A A	BSW
	165/65R14		79T	569	22.4	160	6.3	5	4.5-6	124	4.9	10	7.6	6.8	44	437	963	420A A	BSW
	175/65R14		82T	584	23	176	6.9	5	5-6	136	5.4	10	7.7	6.9	44	475	1047	420A A	BSW
	175/65R14		86T XL	584	23	176	6.9	5	5-6	136	5.4	10	7.7	7.2	50	530	1168	420A A	BSW
	185/65R14		86H	595	23.4	185	7.3	5.5	5-6.5	146	5.7	10	7.6	7.9	44	530	1168	420A A	BSW
	185/65R14		86T	595	23.4	185	7.3	5.5	5-6.5	146	5.7	10	8.2	7.8	44	530	1168	420A A	BSW
	195/65R14		89H	611	24	196	7.7	6	5.5-6.5	152	6	10	8.2	8.3	44	580	1279	420A A	BSW
	215/65R14		94H	638	25.1	218	8.6	6.5	6-7	167	6.6	11	8.5	10	44	670	1477	420A A	BSW
	185/65R15		88H	623	24.5	185	7.3	5.5	5-6	144	5.7	10	8.1	8.4	44	560	1235	420A A	BSW
	195/65R15		91H	636	25	201	7.9	6	5.5-7	145	5.7	10	8.2	8.9	44	615	1355	420A A	BSW
	195/65R15		91T	636	25	201	7.9	6	5.5-7	145	5.7	10	8.2	8.8	44	615	1355	420A A	BSW

SER	Size	PR	L/SS	Overall		Section		Standard	Approved	Tread		Tread		Weight	MAX.	Max		UTQG	Sidewall Type
				Diameter		Width		Rim	Rim Width	Width		Depth			PSI	Load			
				mm	in	mm	in	in	in	mm	in	in32"	mm		KG	COLD	KGS		
	195/65R15		95T XL	636	25	201	7.9	6	5.5-7	145	5.7	10	8.2	9.3	50	690	1521	420A A	BSW
	205/65R15		95H	647	25.5	205	8.1	6	5.5-6.5	162	6.4	10	8	9.6	44	690	1521	420A A	BSW
	215/65R15		96H	663	26.1	216	8.5	6.5	6-7	167	6.6	11	8.5	10.8	44	710	1565	420A A	BSW
	215/65R16		98H	686	27	219	8.6	6.5	6-7.5	160	6.3	10	7.9	10.9	44	750	1653	420A A	BSW
70	145/70R12		69T	512	20.2	148	5.8	4.5	45	105	4.1	8.8	7	5.2	44	325	716	420A A	BSW
	145/70R13		71T	535	21.1	152	6	4.5	45	105	4.2	9	7.4	5.6	44	345	760	420A A	BSW
	155/70R13		75T	546	21.5	160	6.3	4.5	45	113	4.4	10	7.8	6.1	44	387	853	420A A	BSW
	165/70R13		79T	560	22	170	6.7	5	4.55.5	120	4.7	10	7.9	6.6	44	437	963	420A A	BSW
	175/70R13		82T	581	22.9	173	6.8	5	4.5-5.5	127	5	10	7.7	7	44	475	1047	420A A	BSW
	185/70R13		86T	589	23.2	192	7.6	5.5	56	134	5.3	10	7.9	7.4	44	530	1168	420A A	BSW
	165/70R14		81T	589	23.2	171	6.7	5	4.55.5	120	4.7	10.1	8	6.7	44	462	1019	420A A	BSW
	165/70R14		85T XL	587	23.1	171	6.7	5	4.55.5	120	4.7	9.2	7.3	6.9	50	515	1135	420A A	BSW
	175/70R14		84T	602	23.7	180	7	5	4.55.5	127	5	10	8.1	7.6	44	500	1102	420A A	BSW
	185/70R14		88T	619	24.4	194	7.6	5.5	56	132	5.2	10	8.2	8.2	44	560	1235	420A A	BSW
	195/70R14		91T	629	24.8	202	8	6	5.56.5	138	5.4	10	8.4	9.3	44	615	1356	420A A	BSW
	205/70R14		95T	645	25.4	211	8.3	6	5.56.5	149	5.9	9	7.2	10	44	690	1521	420A A	BSW
	205/70R15		96T	666	26.3	211	8.3	6	5.56.5	149	5.9	10	8.1	10.8	44	710	1565	420A A	BSW
215/70R15		98T	681	26.8	226	8.9	6.5	67	156	6.1	10	8.1	11.5	44	750	1653	420A A	BSW	
80	155/80R12		77T	553	21.8	159	6.3	4.5	45	107	4.2	9	7.5	6.1	44	412	908	420A A	BSW
	135/80R13		70T	546	21.5	138	5.4	3.5	3.54.5	93	3.7	9	7.3	5.3	44	335	739	420A A	BSW
	145/80R13		75T	562	22.1	149	5.9	4	3.54.5	101	3.9	9	7.4	5.7	44	387	853	420A A	BSW
	155/80R13		79T	578	22.8	159	6.3	4.5	45	107	4.2	9	7.5	6.7	44	437	963	420A A	BSW
	165/80R13		83T	594	23.4	168	6.6	4.5	45	114	4.4	9	7.6	7.3	44	487	1073	420A A	BSW
	175/80R14		88T	636	25	179	7	5	4.55	121	4.8	9	7.7	7.9	44	560	1235	420A A	BSW
	185/80R14		91T	650	25.6	189	7.4	5	4.55.5	128	5	10	7.9	9.2	44	615	1356	420A A	BSW
	165/80R15		87T	644	25.4	171	6.7	4.5	45	114	4.5	10	8.1	8	44	545	1201	420A A	BSW
	185/80R15		93T	677	26.7	150	5.9	5	4.55.5	128	5	10	7.6	10	44	650	1433	420A A	BSW

*These data can be changed by manufacturer without prior notice.

Update: 2016/03/31