

Couragia F/X - Global Market Dimension Data (30/35/40/45/50/55/60/65)

SER	Size	PR	LI/SS	Overall		Section		Standard	Approved	Tread		Tread		Weight	MAX.	Max		UTQG	Sidewall Type
				Diameter		Width		Rim	Rim Width	Width		Depth			PSI	Load			
				mm	in	mm	in	in	in	mm	in	in32"	mm		KG	COLD	KGS		
30	295/30ZR22		103W XL	741	29.2	299	11.8	10.5	10-11.5	273	10.7	10	7.6	16.7	50	875	1929	320A A	BSW
35	315/35ZR20		106W	726	28.6	322	12.7	11	10.5-12.5	141	5.6	9	7.5	17.5	44	950	2094	320A A	BSW
	295/35ZR21		107Y XL	740	29.1	294	11.6	10.5	10-11.5	260	10.2	9	7.1	16.9	50	975	2150	320A A	BSW
	265/35ZR22		102W XL	745	29.3	268	10.6	9.5	9-10	238	9.4	10	8	16.6	50	850	1874	320A A	BSW
	285/35ZR22		106W XL	761	30	284	11.2	10	9.5-11	254	10	9	7.4	17.1	44	950	2094	320A A	BSW
40	255/40ZR20		101Y XL	711	28	263	10.3	9	8.5-10	212	8.3	10	7.7	13.8	50	825	1819	320A A	BSW
	275/40ZR20		106W XL	726	28.6	275	10.8	9.5	9-10	225	8.9	10	8.3	15.5	50	950	2095	320A A	BSW
	295/40ZR21		111W XL	770	30.3	297	11.7	10.5	10-11.5	247	9.7	10	7.7	16.7	50	1090	2403	320A A	BSW
	265/40R22		106V XL	775	30.5	268	10.5	9.5	9-10.5	221	8.7	10	7.7	15.5	50	950	2094	320A A	BSW
	305/40R22		114V XL	803	31.6	309	12.1	11	10-12	256	10.1	10	7.7	19.6	50	1180	2601	320A A	BSW
45	255/45R18		99V	690	27.1	251	9.9	8.5	8-9	211	8.3	10	8.2	13.8	44	775	1709	320A A	BSW
	275/45R19		108Y XL	736	29	268	10.6	9	8.5-10.5	227	8.9	10	8.2	15.4	50	1000	2205	320A A	BSW
	285/45ZR19		111W XL	739	29.1	285	11.2	9.5	9-10.5	238	9.4	10	8.1	15.7	50	1090	2403	320A A	BSW
	255/45R20		105V XL	740	29.1	249	9.8	8.5	8.5-10	211	8.3	10	8.2	14.9	50	925	2039	320A A	BSW
	265/45R20		108H XL	750	29.5	265	10.4	9	8.5-10	221	8.7	10	8.2	14.2	50	1000	2205	320A A	BSW
	275/45R20		110V XL	755	29.7	269	10.6	9	8.5-10	228	9	10	7.6	16.4	50	1060	2337	320A A	BSW
	295/45R20		114V XL	777	30.6	301	11.8	10	9.5-11	246	9.7	11	8.6	17.6	50	1180	2601	320A A	BSW
	275/45R22		112V XL	812	32	263	10.4	9	8.5-10.5	226	8.9	10	7.6	17	50	1120	2469	320A A	BSW
	285/45R22		114V XL	820	32.3	282	11.1	9.5	9-10.5	237	9.3	11	8.6	17.8	50	1180	260	320A A	BSW
	305/45R22		118V XL	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	20.6	50	1320	2910	320A A	BSW
50	235/50R18		97V	696	27.4	238	9.4	7.5	6.5-8.5	195	7.7	10	7.7	12.1	44	730	1609	320A A	BSW
	235/50R19		99V	721	28.4	242	9.5	7.5	6.5-8.5	196	7.7	10	7.7	12.7	44	775	1709	320A A	BSW
	255/50ZR19		107W XL	737	29	260	10.2	8	7.5-8.5	226	8.9	10	8.3	15.3	50	975	2150	320A A	BSW
	265/50R19		110V XL	753	29.6	271	10.7	8.5	7.5-9.5	222	8.7	10	7.8	14.6	50	1060	2337	320A A	BSW
	265/50R20		112V XL	774	30.5	274	10.8	8.5	7.5-9.5	222	8.7	10	7.7	17.6	50	1120	2469	320A A	BSW
	285/50R20		116V XL	797	31.4	291	11.4	9	8-10	237	9.3	10	8.2	18.1	50	1250	2756	320A A	BSW
55	255/55ZR18		109Y XL	736	29	279	11	8	7.5-8.5	240	9.4	10	8.3	15.7	50	1030	2270	320A A	BSW
	235/55ZR19		105W XL	742	29.2	243	9.6	7.5	6.5-8.5	208	8.2	10	7.7	N/A	50	925	2039	320A A	BSW
	245/55R19		103V	755	29.7	246	9.7	7.5	7-8.5	215	8.5	10	7.7	15.4	44	875	1929	320A A	BSW
	255/55R19		111V XL	769	30.3	263	10.4	8	7-9	225	8.9	10	7.7	16.2	50	1090	2403	320A A	BSW
	275/55R19		111V	789	31.1	284	11.2	8.5	7.5-9.5	241	9.5	10	7.7	17.3	44	1090	2403	320A A	BSW

SER	Size	PR	LI/SS	Overall		Section		Standard	Approved	Tread		Tread		Weight	MAX.	Max		UTQG	Sidewall Type
				Diameter		Width		Rim	Rim Width	Width		Depth			PSI	Load			
				mm	in	mm	in	in	in	mm	in	in32"	mm		KG	COLD	KGS		
	275/55R20		117V XL	813	32	280	11	8.5	7.5-9.5	226	8.9	10	8	18.3	50	1285	2833	320A A	BSW
60	235/60R18		107V XL	733	28.9	240	9.4	7	6.5-7.5	203	8	10	8.3	14.1	50	975	2150	320A A	BSW
	275/60R20		119V XL	840	33.1	270	10.6	8	7.5-9.5	220	8.7	10	8.3	19.3	50	1360	2998	320A A	BSW
65	235/65R17		108V XL	734	28.9	240	9.4	7	6.5-7.5	191	7.5	10	8.3	13.5	50	1000	2205	320A A	BSW
	225/65R18		103H	755	29.7	221	8.7	6.5	6-8	176	6.9	10	8	12.5	44	875	1929	320A A	BSW

*These data can be changed by manufacturer without prior notice.

Update: 2016/03/31