

Couragia A/T - Global Market Dimension Data (70/75/80/85)

SER	Size	PR	L/SS	Overall		Section		Standard	Approved	Tread		Tread		Weight	MAX.	Max		UTQG	Sidewall Type
				Diameter		Width		Rim	Rim Width	Width	Depth	PSI	Load						
				mm	in	mm	in	in	in	mm	in	in32"	mm		KG	COLD	KGS		
70	P205/70R15		96T	668	26.3	207	8.1	6	5-7	165	6.5	12	9.7	11.5	44	710	1565	480A B	BSW
	P215/70R16		100T	708	27.9	221	8.7	6.5	6-7	174	6.9	13	10.1	14.4	44	800	1763	480A B	OWL
	P225/70R16		101S	721	28.4	231	9.1	6.5	6-7.5	179	7	13	10.2	14.5	44	825	1819	480A B	OWL
	P235/70R16		106S	736	29	235	9.3	7	6.5-7.5	185	7.3	13	10	15.2	44	950	2094	480A B	OWL
	P245/70R16		112S XL	748	29.5	245	9.6	7	6.5-7.5	195	7.7	13	10	17.2	50	1120	2469	480A B	OWL
	P255/70R16		111S	764	30.1	260	10.2	7.5	7-8	205	8.1	13	10	17.4	44	1090	2403	480A B	OWL
	P265/70R16		112S	778	30.6	272	10.7	8	7.5-8.5	214	8.4	12	9.8	18.7	44	1120	2469	480A B	OWL
	LT225/70R17	10	116/114Q	750	29.5	226	8.9	6.5	6-7.5	178	7	11	9.1	18	80	1250/1180	2756/2601	N/A	OWL
	LT265/70R17	10	121/118Q	803	31.6	274	10.8	8	7.5-8.5	208	8.2	14	11.2	21.9	80	1450/1320	3197/2910	N/A	OWL
	P265/70R17		115S	804	31.7	272	10.7	8	7.5-8.5	214	8.4	13	10.2	21	44	1215	2679	480A B	OWL
75	LT215/75R15	6	100/97Q	703	27.7	216	8.5	6	5.5-6.5	158	6.2	13	10.3	14.5	50	800/ 730	1765/1610	--	OWL
	LT235/75R15	6	104/101Q	733	28.9	235	9.3	6.5	6-7	173	6.8	14	11.1	15.1	50	900/ 825	1985/1820	--	OWL
	P235/75R15		105S	733	28.9	235	9.3	6.5	6-7	159	6.3	12	9.4	14.6	44	925	2039	480A B	OWL
	LT225/75R16	10	115/112Q	744	29.3	218	8.6	6	5.5-6.5	169	6.7	15	11.6	18.1	80	1215/1120	2679/2469	--	BSW
	LT245/75R16	10	120/116Q	774	30.5	248	9.8	7	6.5-7.5	179	7	16	12.5	18.9	80	1380/1260	3042/2778	--	OWL
	LT265/75R16	10	123/120Q	805	31.7	259	10.2	7.5	7-8	203	8	15	11.8	22.4	80	1550/1400	3417/3086	--	OWL
	LT285/75R16	8	122/119Q	834	32.8	286	11.3	8	7.5-8.5	208	8.2	15	11.9	27.6	65	1500/1360	3305/3000	--	OWL
P265/75R16		116S	804	31.7	267	10.5	7.5	7-8	180	7.1	13	10.4	19.2	44	1250	2756	480A B	OWL	
80	195/80R15		96S	693	27.3	194	7.6	5.5	5-6.5	147	5.8	11	9	11.5	44	710	1565	480A B	BSW
	205/80R16		104S XL	734	28.9	201	7.9	5.5	5-6	152	6	11	8.9	13.6	50	900	1984	480A B	BSW
	30* 9.50R15	6	104Q	756	29.8	240	9.4	7.5	7-8	190	7.5	16	12.7	17.7	50	900	1985	--	OWL
	31*10.50R15	6	109Q	781	30.7	264	10.4	8.5	8-9	212	8.3	16	12.7	20.4	50	1030	227	--	OWL
85	LT215/85R16	10	115/112Q	774	30.5	213	8.4	6	5.5-6.5	171	6.7	16	12.4	18.6	80	1215/1120	2679/2469	--	BSW
	LT235/85R16	10	120/116Q	806	31.7	235	9.3	6.5	6-7	170	6.7	15	11.9	20.4	80	1380/1260	3042/2778	--	BSW

*These data can be changed by manufacturer without prior notice.

Update: 2016/03/31