

Couragia M/T - Global Market Dimension Data (65/70/75/80/85)

SER	Size	PR	L/SS	Overall		Section		Standard	Approved	Tread		Tread		Weight	MAX.	Max		UTQG	Sidewall Type
				Diameter		Width		Rim	Rim Width	Width	Depth	PSI	Load						
				mm	in	mm	in	in	in	mm	in	in32"	mm		KG	COLD	KGS		
65	LT275/65R18	8	119/116Q	824	32.4	275	10.8	8	7.5-9	216	8.5	20	15.6	23.3	65	1360/	2998/	N/A	BSW
	LT275/65R18	10	123/120Q	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	25.2	80	1550/1400	3417/3086	N/A	BSW
70	LT265/70R17	10	121/118Q	810	31.9	272	10.7	8	7-8.5	212	8.3	20	15.9	26.2	80	1450/1320	3195/2910	--	OWL
	LT285/70R17	8	121/118Q	840	33.1	287	11.3	8.5	8-9	228	9	20	15.9	25.6	65	1450/1320	3195/2910	N/A	OWL
75	LT235/75R15	6	104/101Q	734	28.9	228	9	6.5	6-7	168	6.6	19	15	16.8	50	900/ 825	1985/1820	--	OWL
	LT225/75R16	10	115/112Q	752	29.6	215	8.4	6	6-7	160	6.3	19	15	18	80	1215/1120	2679/2469	N/A	BSW
	LT245/75R16	10	120/116Q	781	30.7	244	9.6	6	6.5-8	178	7	19	15	21.3	80	1400/1260	3086/2778	N/A	BSW
	LT265/75R16	8	119/116Q	807	31.8	260	10.2	7.5	7-8	193	7.6	19	15	23.5	65	1360/1250	3000/2755	--	OWL
	LT265/75R16	10	123/120Q	807	31.8	262	10.3	7.5	7-8	193	7.6	19	15	23.5	80	1550/1400	3417/3086	--	OWL
	LT285/75	8	122/119Q	835	32.9	281	11.1	8	7.5-9	208	8.2	19	15	25.2	65	1500/1360	3305/3000	--	OWL
	LT285/75R16	10	126/123Q	835	32.9	281	11.1	8	7.5-9	208	8.2	19	15	25.6	80	1700/1550	3748/3417	--	OWL
	LT315/75	10	127/124Q	881	34.7	317	12.5	8.5	8-11	226	8.9	21	16.3	30.3	65	1750/	3858/	N/A	OWL
80	LT205/80R16	8	110/108Q	734	28.9	210	8.3	5.5	5-7	160	6.3	19	15	16.9	65	1060/1000	2337/2205	--	OWL
	30° 9.50R15	6	104Q	757	29.8	252	9.9	7.5	6.5-8.5	192	7.6	19	15	19.9	35	900	1985	--	OWL
	31°10.50R15	6	109Q	785	30.9	268	10.6	8.5	7-9	200	7.9	19	15	21.9	50	1030	2270	--	OWL
	33°12.50R15	6	108Q	833	32.8	325	12.8	10	8.5-11	248	9.8	19	15	28.7	35	1000	2205	--	OWL
	35°12.50R15	6	113Q	883	34.8	343	13.5	10	9.5-10.5	252	9.9	21	16.7	29.7	35	1150	2535	N/A	BSW
	35°12.50R17	10	125Q	884	34.8	313	12.3	10	9.5-10.5	248	9.8	21	16.7	33.8	65	1650	3637	--	OWL
	37°12.50R17	10	129Q	933	36.7	327	12.9	10	8-11	251	9.9	19	15	35.1	65	1850	4080	N/A	BSW
	35°12.50R18	10	123Q	886	34.9	309	12.2	10	9.5-10.5	248	9.8	21	16.7	34	65	1550	3415	--	BSW
	37°12.50R18	10	128Q	934	36.8	328	12.9	10	8-11	251	9.9	19	15	34.3	65	1800	3970	N/A	BSW
	33°12.50R20	10	114Q	833	32.8	313	12.3	10	9.5-10.5	256	10.1	21	16.7	29.9	65	1180	2600	--	BSW
35°12.50R20	10	121Q	883	34.8	318	12.5	10	8.5-11	256	10.1	21	16.3	31.3	65	1450	3195	--	BSW	
37°12.50R20	10	126Q	934	36.8	320	12.6	10	8.5-11	251	9.9	19	15	32	65	1700	3750	N/A	BSW	
85	LT235/85R16	10	120/116Q	806	31.7	231	9.1	6.5	6-7.5	170	6.7	19	15	21.3	80	1400/1260	3086/2778	--	OBL

*These data can be changed by manufacturer without prior notice.