

Ecovan ER01 - Global Market Dimension Data (65/70/75/80)

SER	Size	PR	LI/SS	Overall		Section		Standard	Approved	Tread		Tread		Weight	MAX.	Max		UTQG	Sidewall Type	
				Diameter		Width		Rim	Rim Width	Width		Depth			PSI	Load				
				mm	in	mm	in	in	in	mm	in	in32"	mm		KG	COLD	KGS			LBS
65	215/60R16C	8	108/106R	664.7	26.2	217.4	8.6	6.5	67	172.6	6.8	13.5	10.7	13.4	69	1000/950	2205/2094			
	70	175/65R14C	6	90/88T	583	22.9	168	6.6	5	4.55.5	130	5.1	12.1	9.6	8.7	54	600/560	1323/1235		
		205/65R16C	8	107/105T	671	26.4	204	8	6	5.56.5	204	8	14	11.1	12.8	69	975/925	2150/2039		
		215/65R16C	8	109/107T	685.7	27	211.8	8.3	6.5	67	165	6.5	13.6	10.8	13.7	69	1030/975	2271/2150		
		225/65R16C	8	112/110R	697	27.4	223	8.8	6.5	67	170	6.7	13.9	11.1	14.4	69	1120/1060	2469/2336		
		235/65R16C	8	115/113R	712.7	28.1	236	9.3	7	6.57.5	180	7.1	13.5	10.7	14.5	69	1215/1150	2678/2535		
		165/70R14C	8	89/87R	589.8	23.2	165.8	6.5	5	4.55.5	123.7	4.9	10.2	8.1	8.8	55	580/545	1279/1202		
		195/70R15C	8	104/102R	656.1	25.8	199.1	7.8	6	5.56.5	146	5.7	11.5	9.1	12.5	65	900/850	1981/1874		
		205/70R15C	8	106/104S	669	26.3	210	8.3	6.5	67	210	8.3	12.3	9.8	13.1	54	950/900	2094/1984		
		#215/70R15C	6	106/104R	683.7	26.9	216.8	8.5	6.5	67	162	6.4	10	8	12.9	54	950/900	2094/1984		
		215/70R15C	8	109/107R	684.1	26.9	223	8.8	6.5	67	162	6.4	12.3	9.8	13.6	65	1030/975	2270/2149		
225/70R15C	8	112/110R	697	27.4	230	9.1	6.5	67	230	9.1	13.1	10.4	15	54	1120/1060	2469/2336				
75	205/75R14C	8	109/107Q	663.4	26.1	197.5	7.8	5.5	56	144	5.7	13	10.3	12.5	69	1030/975	2271/2150			
	215/75E14C	8	112/110Q	679.3	26.7	209.6	8.3	6	5.56.5	154	6.1	13	10.7	13.6	69	1120/1060	2469/2336			
	175/75R16C	8	101/99R	669.1	26.3	170.1	6.7	5	4.55.5	125	4.9	13.7	10.9	11.1	69	825/775	1819/1709			
	185/75R16C	8	104/102R	684.1	26.9	178.6	7	5	4.55.5	130	5.1	12.9	10.3	12	69	900/850	1984/1874			
	195/75R16C	10	110/108R	698.1	29.5	189.6	7.5	5.5	56	129	2.5	13.5	10.7	12.5	76	1060/1000	2337/2205			
	205/75R16C	8	110/108R	714.7	28.1	208.2	8.2	6.5	67	144	5.7	13.7	10.9	14.2	69	1060/1000	2337/2205			
	215/75R16C	8	116/114R	727.7	28.9	214.2	8.4	6	5.56.5	154	6.1	13.5	10.8	15.4	76	1520/1180	2756/2601			
225/75R16C	10	121/120R	745.5	29.4	216.3	8.5	6	5.56.5	215	8.5	13.2	10.5	17.1	83	1450/1400	3197/3086				
80	145R12C	8	86/84P	539.5	21.2	149.3	5.9	4	3.44	109	4.3	10.9	8.7	7	65	530/500	1168/1102			
	155R12C	8	88/86P	552.6	21.8	161.8	6.4	4.5	44.5	116	4.6	11.2	8.9	7.8	65	560/530	1235/1168			
	155R13C	8	90/88P	581.8	22.9	159.9	6.3	4.5	4.55	160	6.3	9.7	7.7	8.2	65	600/560	1323/1235			
	165R13C	8	94/92Q	601.3	23.7	172	6.8	4.5	4.55	124	4.9	10	7.9	9.2	65	670/630	1477/1289			
	175R13C	8	97/95Q	608.6	24	175.3	6.9	5	4.55.5	130	5.1	11.8	9.4	10	65	730/690	1610/1521			
	185R13C	8	100/98Q	626.8	24.7	194.5	7.7	5.5	56	138	5.4	12.6	10	10.5	65	800/750	1764/1654			
	165R14C	8	97/95Q	624.8	24.6	171	6.7	4.5	45	124	4.9	12	9.6	9.6	65	730/690	1609/1521			
	175R14C	8	99/98Q	635.9	25	135.2	5.3	5	4.55.5	121	4.8	11.5	9.2	10.4	65	775/750	1709/1654			
	185R14C	8	102/100R	649.7	25.6	192.5	7.6	5.5	56	138	5.4	12.3	9.8	11.4	65	850/800	1873/1763			
	195R14C	8	106/104R	666	26.2	200	7.9	5.5	56	200	7.9	13.2	10.5	12.9	65	950/900	2094/1984			
205R14C	8	109/107P	681.5	26.8	209.8	8.3	6	5.56.5	154	6.1	12.8		13.8	65	1030/975	2270/2149				

SER	Size	PR	LI/SS	Overall		Section		Standard	Approved	Tread		Tread		Weight	MAX.	Max		UTQG	Sidewall Type
				Diameter		Width		Rim	Rim Width	Width		Depth			PSI	Load			
				mm	in	mm	in	in	in	mm	in	in32"	mm	KG	COLD	KGS	LBS		
	215R14C	8	112/110Q	700.9	27.6	221.3	8.7	6	5.57	163	6.4	12.8	10.2	14.7	65	1120/1060	2469/2336		
	185R15C	8	103/102R	675.6	26.6	194.2	7.6	5.5	56	138	5.4	14.1	11.2	12.4	65	875/850	1929/1874		
	195R15C	8	106/104R	690.3	27.2	201.8	7.9	5.5	56	146	5.7	13.6	10.8	13.9	65	950/900	2094/1984		
	*LT5.00R12	8	83/81P	567.8	22.4	144	5.7	3.5	34	105	4.1	10.8	8.6	7.5	65	487/462	1074/1019		

*These data can be changed by manufacturer without prior notice.

Update: 2016/03/31