

MR295 - Global Market Dimension Data (100)

SER	Size	PR	L/SS	Overall		Section		Standard	Approved	Tread		Tread		Weight	MAX.	Max		UTQG	Sidewall Type
				Diameter		Width		Rim	Rim Width	Width		Depth			PSI	Load			
				mm	in	mm	in	in	in	mm	in	in32"	mm		KG	COLD	KGS		
100	700-R15	10	110/109M	755	29.7	197	7.8	5.5	5-6	134	5.3	13	10.5	17.6	76	1080/1030	2381/2271	N/A	BSW
	700R16	12	117/116M	781	30.7	197	7.8	5.5	5-6	134	5.3	13	10.5	19	87	1285/1250	2830/2753	N/A	BSW
	LT6.50R15	10	108/107N	720	28.4	179.0	7.0	5.5	6.06.0	127	5.0	13.0	10.2	15.700	80	1000/975	2205/2150	N/A	N/A
	LT6.50R16	10	107/102Q	746	29.4	188.0	7.4	5.5	5.05.0	127	5.0	12.7	10.5	15.800	81	975/850	2150/1874	N/A	N/A
	LT7.00R15	10	111/109M	750	29.5	182.0	7.2	5.5	6.06.0	152	6.0	13.2	10.5	18.100	76	1080/1030	2381/2271	N/A	N/A
	LT7.00R16	12	117/116N	774	30.5	196.0	7.7	5.5	6.06.0	152	6.0	13.0	10.3	21.300	87	1285/1250	2833/2756	N/A	N/A
	LT7.00R16	12	121/120M	806	31.7	198.0	7.8	6	5.06.0	146	5.7	14.2	11.3	23	90	1450/1400	3196/3086	N/A	N/A

*These data can be changed by manufacturer without prior notice.

Update: 2016/03/31