

# 595RS-RR - Global Market Dimension Data (35/40/45/50)

[Print](#)

SER	Size	PR	LI/SS	Overall Diameter		Section Width		Standard Rim	Approved Rim Width	Tread Width		Tread Depth		Weight	MAX. PSI	Max Load		UTQG	Sidewall Type
				mm	in	mm	in	in	in	mm	in	in32"	mm	KG	COLD	KGS	LBS		
35	245/35ZR18		92W XL	627	24.7	246	9.7	8.5	8-9.5	228	9	7	5.8	11.4	50	630	1389	140AA A	BSW
	255/35ZR18		94W XL	637	25.1	260	10.2	9	8.5-10	239	9.4	7	5.8	12.5	50	670	1477	140AA A	BSW
	265/35ZR18		97W XL	643	25.3	271	10.7	9.5	9-10.5	248	9.8	7	5.8	12.4	50	730	1609	140AA A	BSW
	275/35ZR18		95W	649	25.5	278	10.9	9.5	9-11	256	10.1	7	5.8	12.8	44	690	1521	140AA A	BSW
	235/35ZR19		91W XL	649	25.5	236	9.3	8.5	8-9.5	222	8.7	7	5.8	11.2	50	615	1356	140AA A	BSW
	255/35ZR19		96W XL	662	26.1	257	10.1	9	8.5-10	239	9.4	7	5.8	12.1	50	710	1565	140AA A	BSW
	265/35ZR19		94W	669	26.3	271	10.7	9.5	9-10.5	249	9.8	7	5.8	12.8	44	670	1477	140AA A	BSW
	275/35ZR19		96W	675	26.6	277	10.9	9.5	9-11	256	10.1	7	5.8	13.3	44	710	1565	140AA A	BSW
40	215/40ZR17		87W XL	606	23.9	216	8.5	7.5	7-8.5	196	7.7	7	5.8	10	50	545	1202	140AA A	BSW
	235/40ZR17		90W	617	24.3	246	9.7	8.5	8-9.5	220	8.7	7	5.8	11.2	44	600	1323	140AA A	BSW
	255/40ZR17		94W	634	25	263	10.3	9	8.5-10	236	9.3	7	5.8	12.2	44	670	1477	140AA A	BSW
	215/40ZR18		85W	630	24.8	216	8.5	7.5	7-8.5	196	7.7	7	5.8	10.6	44	515	1135	140AA A	BSW
	225/40ZR18		92W XL	637	25.1	234	9.2	8	7.5-9	206	8.1	7	5.8	10.8	50	630	1389	140AA A	BSW
	235/40ZR18		91W	642	25.3	246	9.7	8.5	8-9.5	220	8.7	7	5.8	11.5	44	615	1356	140AA A	BSW
	245/40ZR18		93W	652	25.7	249	9.8	8.5	8-9.5	223	8.8	7	5.8	12.1	44	650	1433	140AA A	BSW
	265/40ZR18		101W XL	668	26.3	273	10.7	9.5	9-10.5	244	9.6	7	5.8	13.2	50	825	1819	140AA A	BSW
	245/40ZR19		98W XL	680	26.8	245	9.6	8.5	8-9.5	223	8.8	7	5.8	12.3	50	750	1653	140AA A	BSW
45	215/45ZR17		87W	626	24.7	216	8.5	7	7-8	196	7.7	7	5.8	10.7	44	545	1202	140AA A	BSW

SER	Size	PR	LI/SS	Overall Diameter		Section Width		Standard Rim	Approved Rim Width	Tread Width		Tread Depth		Weight	MAX. PSI	Max Load		UTQG	Sidewall Type
				mm	in	mm	in	in	in	mm	in	in32"	mm	KG	COLD	KGS	LBS		
	225/45ZR17		94W XL	633	24.9	227	9	7.5	7-8.5	208	8.2	7	5.8	11	50	670	1477	140AA A	BSW
	235/45ZR17		94W	642	25.3	242	9.5	8	7.5-9	216	8.5	7	5.8	11.7	44	670	1477	140AA A	BSW
<b>50</b>	205/50ZR15		89W XL	586	23.1	210	8.3	6.5	5.5-7.5	182	7.2	7	5.8	9.7	50	580	1279	140AA A	BSW

\*These data can be changed by manufacturer without prior notice.

Update: 2016/03/31