

EVOLUZIONE ST-1 - Global Market Dimension Data (30/35/40/45/50/55)

SER	Size	PR	LI/SS	Overall Diameter		Section Width		Standard Rim	Approved Rim Width	Tread Width		Tread Depth		Weight	MAX. PSI	Max Load		UTQG	Sidewall Type
				mm	in	mm	in	in	in	mm	in	in32"	mm	KG	COLD	KGS	LBS		
30	255/30ZR20		92Y XL	660	26	275	10.8	9	8.5-9.5	235	9.3	10	7.7	11.9	50	630	1388	300AA A	BSW
	265/30ZR19		93Y XL	643	25.3	271	10.7	9.5	9-10	246	9.7	10	7.7	11.6	50	650	1433	300AA A	BSW
	275/30ZR19		96Y XL	648	25.5	277	10.9	9.5	9-10	252	9.9	10	7.7	11.6	50	710	1565	300AA A	BSW
	285/30ZR19		98Y XL	655	25.8	290	11.4	10	9.5-10.5	264	10.4	10	7.7	13.2	50	750	1653	300AA A	BSW
	255/30ZR20		92Y XL	660	26	275	10.8	9	8.5-9.5	235	9.3	10	7.7	11.9	50	630	1388	300AA A	BSW
	275/30ZR20		97Y XL	677	26.7	270	10.6	9.5	9-10	252	9.9	10	7.7	12.5	50	730	1609	300AA A	BSW
	285/30ZR20		99Y XL	681	26.8	285	11.2	10	9.5-10.5	263	10.4	10	7.6	15.2	50	775	1708	300AA A	BSW
35	225/35ZR17		88Y XL	618	24.3	202	7.9	7	6.5-7.5	178	7	10	7.6	N/A	50	560	1234	300AA A	BSW
	215/35ZR18		84Y XL	608	23.9	217	8.5	7.5	7-8.5	186	7.3	10	7.7	9.5	50	500	1102	300AA A	BSW
	225/35ZR18		87Y XL	615	24.2	229	9	8	7.5-9	196	7.7	10	7.7	9.9	50	545	1201	300AA A	BSW
	245/35ZR18		92Y XL	632	24.9	246	9.7	8.5	8-9.5	214	8.4	9	7.4	10.9	50	630	1388	300AA A	BSW
	255/35ZR18		94Y XL	634	25	259	10.2	9	8.5-10	222	8.7	9	7.3	11.9	50	670	1477	300AA A	BSW
	265/35ZR18		97Y XL	643	25.3	270	10.6	9.5	9-10.5	232	9.1	9	7.3	11.6	50	730	1609	300AA A	BSW
	285/35ZR18		101Y XL	654	25.7	299	11.8	10	9.5-11	250	9.8	9	7.1	14.2	50	825	1818	300AA A	BSW
	215/35ZR19		85Y XL	634	25	217	8.5	7.5	7-8.5	186	7.3	10	7.7	9.4	50	515	1135	300AA A	BSW
	225/35ZR19		88Y XL	638	25.1	238	9.4	8	7.5-9	196	7.7	10	7.7	9.9	50	560	1234	300AA A	BSW
	235/35ZR19		91Y XL	652	25.7	239	9.4	8.5	8-9.5	206	8.1	10	7.9	10.4	50	615	1355	300AA A	BSW
	245/35ZR19		93Y XL	654	25.8	246	9.7	8.5	8-9.5	212	8.3	9	7.3	10.8	50	650	1433	300AA A	BSW
	255/35ZR19		96Y XL	662	26.1	260	10.2	9	8.5-10	224	8.8	9	7.4	12	50	710	1565	300AA A	BSW
	275/35ZR19		100Y XL	677	26.7	273	10.7	9.5	9-11	238	9.4	9	7.3	13.1	50	800	1763	300AA A	BSW
	225/35ZR20		90Y XL	667	26.3	231	9.1	8	7.5-9	196	7.7	10	7.6	10.9	50	600	1323	300AA A	BSW
	245/35ZR20		95Y XL	680	26.8	246	9.7	8.5	8-9.5	212	8.3	9	7.3	11.6	50	690	1521	300AA A	BSW
	255/35ZR20		97Y XL	691	27.2	255	10.1	9	8.5-10	222	8.7	9	7.3	12.7	50	730	1609	300AA A	BSW
	275/35ZR20		102Y XL	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	13.3	50	850	1874	300AA A	N/A
40	165/40R16		73V XL	542	21.4	174	6.9	6	6-6	148	5.8	10	7.9	6.6	50	365	804	300AA A	BSW
	195/40ZR16		80W XL	565	22.2	201	7.9	7	6.5-7.5	174	6.9	10	7.9	7	50	450	992	300AA A	BSW
	195/40ZR17		81W XL	589	23.2	200	7.9	7	6.5-7.5	174	6.9	10	8	8	50	462	1019	300AA A	BSW
	205/40ZR17		84Y XL	598	23.5	210	8.3	7.5	7-8	184	7.2	10	7.9	8.3	50	500	1102	300AA A	BSW
	215/40ZR17		87Y XL	604	23.8	217	8.5	7.5	7-8.5	190	7.5	10	8	9.4	50	545	1202	300AA A	BSW

SER	Size	PR	LI/SS	Overall Diameter		Section Width		Standard Rim	Approved Rim Width	Tread Width		Tread Depth		Weight	MAX. PSI	Max Load		UTQG	Sidewall Type
				mm	in	mm	in	in	in	mm	in	in32"	mm	KG	COLD	KGS	LBS		
	245/40ZR17		95Y XL	630	24.8	246	9.7	8.5	8-9.5	216	8.5	10	8	11	50	690	1521	300AA A	BSW
	255/40ZR17		98Y XL	638	25.1	257	10.1	9	8.5-10	226	8.9	10	7.9	11	50	750	1653	300AA A	BSW
	275/40ZR17		98Y	655	25.8	277	10.9	9.5	9-11	242	9.5	10	7.9	11.7	44	750	1653	300AA A	BSW
	205/40ZR18		86Y XL	622	24.5	212	8.3	7.5	7-8	184	7.2	10	8	9.1	50	530	1168	300AA A	BSW
	215/40ZR18		89Y XL	631	24.8	218	8.6	7.5	7-8.5	190	7.5	10	7.9	9.9	50	580	1278	300AA A	BSW
	225/40ZR18		92Y XL	641	25.2	224	8.8	8	7.5-9	202	8	10	7.9	10.3	50	630	1388	300AA A	BSW
	235/40ZR18		95Y XL	645	25.4	239	9.4	8.5	8-9.5	210	8.3	10	7.9	10.4	50	690	1521	300AA A	BSW
	245/40ZR18		97Y XL	648	25.5	247	9.7	8.5	8-9.5	216	8.5	10	7.9	11.8	50	730	1609	300AA A	BSW
	265/40ZR18		101Y XL	667	26.3	279	11	9.5	9-10.5	236	9.3	10	8	13.4	50	825	1818	300AA A	BSW
	275/40ZR18		103Y XL	674	26.5	286	11.3	9.5	9-11	242	9.5	10	8	13.8	50	875	1929	300AA A	BSW
	225/40ZR19		93Y XL	665	26.2	228	9	8	7.5-9	202	8	10	7.9	10.8	50	650	1433	300AA A	BSW
	235/40ZR19		96Y XL	674	26.5	239	9.4	8.5	8-9.5	210	8.3	10	7.9	11.4	50	710	1565	300AA A	BSW
	245/40ZR19		98Y	704	27.7	252	9.9	8	7.5-9	211	8.3	10	7.7	11.9	44	750	1653	300AA A	BSW
	245/40ZR19		98Y XL	678	26.7	244	9.6	8.5	8-9.5	216	8.5	10	7.9	11.2	50	750	1653	300AA A	BSW
	255/40ZR19		100Y XL	687	27	257	10.1	9	8.5-10	226	8.9	10	7.9	13.1	50	800	1764	300AA A	BSW
	275/40ZR19		105Y XL	706	27.8	274	10.8	9.5	9-11	242	9.5	10	7.9	13.6	50	925	2039	300AA A	BSW
	245/40ZR20		99Y XL	704	27.7	247	9.7	8.5	8-9.5	216	8.5	10	8	12.9	50	775	1708	300AA A	BSW
	255/40ZR20		101Y XL	711	28	258	10.2	9	8-9.5	226	8.9	10	7.9	13.8	50	825	1818	300AA A	BSW
	275/40ZR20		106Y XL	725	28.5	286	11.3	9.5	9-11	242	9.5	10	8	14.9	50	950	2094	300AA A	BSW
45	195/45R16		84V XL	584	23	190	7.5	6.5	6-7.5	170	6.7	10	7.6	7.6	50	500	1102	300AA A	BSW
	205/45ZR16		87W XL	592	23.3	204	8	7	6.5-7.5	178	7	10	7.6	8.6	50	545	1201	300AA A	BSW
	215/45ZR16		86W	600	23.6	212	8.3	7	7-8	184	7.2	10	7.7	9	44	530	1168	300AA A	BSW
	205/45ZR17		88Y XL	618	24.3	202	7.9	7	6.5-7.5	178	7	10	7.6	8.3	50	560	1234	300AA A	BSW
	215/45ZR17		91Y XL	624	24.6	211	8.3	7	7-8	184	7.2	10	7.6	9.4	50	615	1355	300AA A	BSW
	225/45R17		94Y XL	635	25	224	8.8	7.5	7-8.5	195	7.7	10	7.7	9.6	50	670	1477	300AA A	BSW
	225/45ZR17		94Y XL	633	24.9	223	8.8	7.5	7-8	195	7.7	10	7.7	9.9	50	670	1477	300AA A	BSW
	235/45ZR17		97Y XL	646	25.4	230	9.1	8	7.5-9	204	8	10	7.6	10.7	50	730	1609	300AA A	BSW
	245/45ZR17		99Y XL	652	25.7	239	9.4	8	7.5-9	211	8.3	10	7.6	11.5	50	775	1708	300AA A	BSW
	225/45ZR18		95Y XL	658	25.9	223	8.8	7.5	7-8.5	195	7.7	10	7.6	10.3	50	690	1521	300AA A	BSW
	245/45ZR18		100Y XL	678	26.7	239	9.4	8	7.5-9	211	8.3	10	7.6	12.8	50	800	1763	300AA A	BSW
	225/45ZR19		96Y XL	683	26.9	234	9.2	7.5	7-8.5	195	7.7	10	7.7	10.7	50	710	1565	300AA A	BSW
	245/45ZR19		98Y	704	27.7	252	9.9	8	7.5-9	211	8.3	10	7.7	12.5	44	750	1653	300AA A	BSW

SER	Size	PR	LI/SS	Overall Diameter		Section Width		Standard Rim	Approved Rim Width	Tread Width		Tread Depth		Weight	MAX. PSI	Max Load		UTQG	Sidewall Type
				mm	in	mm	in	in	in	mm	in	in32"	mm	KG	COLD	KGS	LBS		
50	245/45ZR20		103Y XL	726	28.6	252	9.9	8	7.5-9	211	8.3	10	7.7	13.7	50	875	1929	300AA A	BSW
	205/50ZR16		87W	609	24	213	8.4	6.5	5.5-7.5	182	7.2	10	7.9	9.4	44	545	1201	300AA A	BSW
	225/50ZR16		96W XL	632	24.9	230	9.1	7	6-8	198	7.8	10	7.9	10.7	50	710	1565	300AA A	BSW
	205/50ZR17		93Y XL	641	25.2	210	8.2	6.5	5.5-7.5	182	7.2	10	7.9	9.9	50	650	1432	300AA A	BSW
	215/50ZR17		95W XL	647	25.5	222	8.7	7	6-7.5	192	7.6	10	8	10.5	50	690	1521	300AA A	BSW
	225/50ZR17		98Y XL	659	25.9	230	9	7	6-8	198	7.8	10	7.9	11.1	50	750	1653	300AA A	BSW
	235/50ZR17		96Y	667	26.3	245	9.6	7.5	6.5-8.5	208	8.2	10	7.9	12	44	710	1565	300AA A	BSW
55	195/55R16		87V	621	24.4	196	7.7	6	5.5-7	170	6.7	10	7.9	8.6	44	545	1201	300AA A	BSW
	205/55ZR16		94W XL	634	25	209	8.2	6.5	5.5-7.5	184	7.2	10	7.9	10.2	50	670	1477	300AA A	BSW
	215/55ZR16		97Y XL	641	25.3	224	8.8	7	6-7.5	194	7.6	10	7.9	11.2	50	730	1609	300AA A	BSW
	205/55ZR17		95Y XL	657	25.9	213	8.4	6.5	5.5-7.5	184	7.2	10	7.9	10	50	690	1521	300AA A	BSW
	215/55ZR17		98Y XL	667	26.3	225	8.9	7	6-7.5	194	7.6	10	7.9	10.1	50	750	1653	300AA A	BSW

*These data can be changed by manufacturer without prior notice.

Update: 2019/04/19