

EVOLUZIONE F60 - Global Market Dimension Data (30/35/45)

[Print](#)

SER	Size	PR	LI/SS	Overall Diameter		Section Width		Standard Rim	Approved Rim Width	Tread Width		Tread Depth		Weight	MAX. PSI	Max Load		UTQG	Sidewall Type
				mm	in	mm	in	in	in	mm	in	in32"	mm	KG	COLD	KGS	LBS		
30	295/30ZR20		101Y XL	691	27.2	294	11.6	10.5	N/A	N/A	N/A	N/A	N/A	14.5	50	825	1819	240AA A	N/A
	305/30ZR20		103Y XL	694	27.3	306	12	11	N/A	N/A	N/A	N/A	N/A	14.6	50	875	1929	240AA A	N/A
35	235/35ZR19		91Y XL	648	25.5	243	9.6	8.5	N/A	N/A	N/A	N/A	N/A	10.9	50	615	1356	240AA A	N/A
	255/35ZR19		96Y XL	665	26.2	256	10.1	9	N/A	N/A	N/A	N/A	N/A	12.6	50	710	1565	240AA A	N/A
	265/35ZR19		98Y XL	670	26.4	269	10.6	9.5	N/A	N/A	N/A	N/A	N/A	13.2	50	750	1653	240AA A	N/A
	285/35ZR19		103Y XL	686	27	282	11.1	10	N/A	N/A	N/A	N/A	N/A	13.7	50	875	1929	240AA A	N/A
	235/35ZR20		92Y XL	676	26.6	235	9.3	8.5	N/A	N/A	N/A	N/A	N/A	11.8	50	630	1389	240AA A	N/A
	235/35ZR20		92Y XL	676	26.6	235	9.3	8.5	N/A	N/A	N/A	N/A	N/A	11.8	50	630	1389	240AA A	N/A
45	245/45ZR20		103Y XL	731	28.8	236	9.3	8	N/A	N/A	N/A	N/A	N/A	13.2	50	875	1929	240AA A	N/A

*These data can be changed by manufacturer without prior notice.